



ELECTRA E4

A U D I O

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



DRIVER SPECIFICATIONS

- Titanium-coated injection polypropylene cone with rubber surround
- Powder-coated steel basket
- 26 mm voice coil

Fs	99.26 Hz
Re	3.36 Ohms
Qms	6.23
Qes	1.14
Qts	0.97
Le	0.12 mH
Vas	2.23 liter
Mms	6.85 gram
Cms	375 uM/Newton
Bl	3.55 Tesla-M
SPLref	87.6 (2.83 volts at 1 meter)
Sd	65 sq cm
Xmax	2 mm
Xsus	9

Nominal Power	40 watts
Maximum Power	80 watts
Outside Diameter	102 mm basket + 130 mm ears
Mount Hole	94.5 mm
Mount Depth	52 mm
Weight	567 gram

CROSSOVER, SINGLE AMP OR BI AMP

- 3000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

COMPONENT TWEETER

- 25 mm Aluminum dome
- 4 ohm

Outside Diameter	48.2 mm
Mount Hole	43.5 mm
Mount Depth	11 mm
Weight	50 gram

