



# ELECTRA E5

A U D I O

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



## DRIVER SPECIFICATIONS

- Titanium-coated injection polypropylene cone with rubber surround
- Powder-coated steel basket
- 26 mm voice coil

Fs	74.66 Hz
Re	3.3 Ohms
Qms	2.98
Qes	0.6
Qts	0.5
Le	0.16 mH
Vas	5.66 liter
Mms	10.19 gram
Cms	446 uM/Newton
Bl	5.14 Tesla-M
SPLref	90.8 (2.83 volts at 1 meter)
Sd	95 sq cm
Xmax	2.5 mm
Xsus	10 mm

Nominal Power	50 watts
Maximum Power	100 watts
Outside Diameter	130 mm basket + 150 mm ears
Mount Hole	117 mm
Mount Depth	61 mm
Weight	850 gram

## CROSSOVER, SINGLE AMP OR BI AMP

- 3000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

## COMPONENT TWEETER

- 25 mm Aluminum dome
- 4 ohm

Outside Diameter	48.2 mm
Mount Hole	43.5 mm
Mount Depth	11 mm
Weight	50 gram

