



ELECTRA E6

A U D I O

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



DRIVER SPECIFICATIONS

- Titanium-coated injection polypropylene cone with rubber surround
- Powder-coated steel basket
- 26 mm voice coil

Fs	84.59 Hz
Re	3.4 Ohms
Qms	6.77
Qes	1.08
Qts	0.93
Le	0.15 mH
Vas	7.15 liter
Mms	13.06 gram
Cms	271 uM/Newton
Bl	4.67 Tesla-M
SPLref	90.8 (2.83 volts at 1 meter)
Sd	137 sq cm
Xmax	2.5 mm
Xsus	10 mm

Nominal Power	60 watts
Maximum Power	120 watts
Outside Diameter	166 mm
Mount Hole	144 mm
Mount Depth	66 mm
Weight	993 gram

CROSSOVER, SINGLE AMP OR BI AMP

- 3000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

COMPONENT TWEETER

- 25 mm Aluminum dome
- 4 ohm

Outside Diameter	48.2 mm
Mount Hole	43.5 mm
Mount Depth	11 mm
Weight	50 gram

