



ELECTRA E69 CX

A U D I O

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



DRIVER SPECIFICATIONS

- Titanium coated injection polypropylene cone with rubber surround
- Powder-coated steel basket
- 38 mm voice coil

| | |
|--------|------------------------------|
| Fs | 55.77 Hz |
| Re | 3.35 Ohms |
| Qms | 5.17 |
| Qes | 1.36 |
| Qts | 1.08 |
| Le | 0.28 mH |
| Vas | 22.7 liter |
| Mms | 28.71 gram |
| Cms | 342 uM/Newton |
| Bl | 4.74 Tesla-M |
| SPLref | 88.2 (2.83 volts at 1 meter) |
| Sd | 217 sq cm |
| Xmax | 5.5 mm |
| Xsus | 14 mm |

| | |
|------------------|--------------|
| Nominal Power | 100 watts |
| Maximum Power | 200 watts |
| Outside Diameter | 243 x 173 mm |
| Mount Hole | 215 x 147 mm |
| Mount Depth | 93 mm |
| Weight | 1750 gram |

INTEGRATED CROSSOVER

- 12kHz, 6dB Butterworth
- Polyester capacitor
- Tweeter overload protection

COAXIAL TWEETER

- 25 mm Aluminum dome
- 4 Ohm

