



LUCCENT L5 CX

A U D I O

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



DRIVER SPECIFICATIONS

- Black polypropylene cone with rubber surround
- Cast aluminum basket
- 26 mm voice coil

Fs	87.73 Hz
Re	3.89 Ohms
Qms	10.38
Qes	1.38
Qts	1.22
Le	0.20 mH
Vas	3.64 liter
Mms	11.48 gram
Cms	287 uM/Newton
Bl	4.22 Tesla-M
SPLref	87.3 (2.83 volts at 1 meter)
Sd	95 sq cm
Xmax	5.5 mm
Xsus	10 mm

Nominal Power	75 watts
Maximum Power	150 watts
Outside Diameter	129 mm basket + 149.2 mm ears
Mount Hole	120 mm
Mount Depth	62.4 mm
Weight	355 gram

CROSSOVER, SINGLE AMP OR BI AMP

- 3000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

POINT SOURCE TWEETER

- 14 mm silk dome
- 4 Ohm

