



# LUCCENT L6

AUDIO

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



## DRIVER SPECIFICATIONS

- Black polypropylene cone with rubber surround
- Cast aluminum basket
- 38 mm voice coil

Fs	64.78 Hz
Re	3.58 Ohms
Qms	12.3
Qes	0.84
Qts	0.78
Le	0.22 mH
Vas	7.54 liter
Mms	18.64 gram
Cms	324 uM/Newton
Bl	5.69 Tesla-M
SPLref	88.7 (2.83 volts at 1 meter)
Sd	128 sq cm
Xmax	5 mm
Xsus	12 mm

Nominal Power	100 watts
Maximum Power	200 watts
Outside Diameter	166.5 mm
Mount Hole	137.4 mm
Mount Depth	53.3 mm
Weight	650 gram

## CROSSOVER, SINGLE AMP OR BI AMP

- 2000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

## COMPONENT TWEETER

- 25 mm Silk Dome
- Low resonance frequency air chamber
- 4 ohm

Outside Diameter	48.2 mm
Mount Hole	43.5 mm
Mount Depth	24 mm
Weight	50 gram

