



# CARBON C6 CX

AUDIO

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



## DRIVER SPECIFICATIONS

- Woven carbon fiber cone with rubber surround
- Cast aluminum basket
- 38 mm voice coil

Fs	68.36 Hz
Re	3.03 Ohms
Qms	12.46
Qes	0.79
Qts	0.74
Le	0.20 mH
Vas	5.98 liter
Mms	21 gram
Cms	257 uM/Newton
Bl	5.9 Tesla-M
SPLref	88.7 (2.83 volts at 1 meter)
Sd	128.7 sq cm
Xmax	7.7 mm
Xsus	10 mm

Nominal Power	100 watts
Maximum Power	200 watts
Outside Diameter	166.5 mm
Mount Hole	137.4 mm
Mount Depth	80.3 mm
Weight	770 gram

## CROSSOVER, SINGLE AMP OR BI AMP

- 3000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

## POINT SOURCE TWEETER

- 25 mm Beryllium Copper
- 4 Ohm

