



AUDIO

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM

LUCCENT L6



DRIVER SPECIFICATIONS

- Black polypropylene cone with rubber surround
- Cast aluminum basket
- 38 mm voice coil

Fs	64.78 Hz
Re	3.58 Ohms
Qms	12.3
Qes	0.84
Qts	0.78
Le	0.22 mH
Vas	7.54 liter
Mms	18.64 gram
Cms	324 uM/Newton
Bl	5.69 Tesla-M
SPLref	88.7 (2.83 volts at 1 meter)
Sd	128 sq cm
Xmax	5 mm
Xsus	12 mm

Nominal Power	100 watts
Maximum Power	200 watts
Outside Diameter	166.5 mm
Mount Hole	137.4 mm
Mount Depth	53.3 mm
Weight	650 gram

CROSSOVER, SINGLE AMP OR BI AMP

- 2000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

COMPONENT TWEETER

- 25 mm Black Aluminum
- Low resonance frequency air chamber
- 4 ohm

Outside Diameter	48.2 mm
Mount Hole	43.5 mm
Mount Depth	24 mm
Weight	50 gram

