



LUCCENT L6 CX

A U D I O

804 CALLE PLANO, CAMARILLO, CA 93012 - 888.340.4403 - WWW.ILLUSIONAUDIO-AMERICA.COM



DRIVER SPECIFICATIONS

- Black polypropylene cone with rubber surround
- Cast aluminum basket
- 38 mm voice coil

Fs	68.19 Hz
Re	2.93 Ohms
Qms	10.33
Qes	0.79
Qts	0.73
Le	0.20 mH
Vas	6.69 liter
Mms	18.95 gram
Cms	287 uM/Newton
Bl	5.5 Tesla-M
SPLref	89.1 (2.83 volts at 1 meter)
Sd	128.7 sq cm
Xmax	7.7 mm
Xsus	12 mm

Nominal Power	100 watts
Maximum Power	200 watts
Outside Diameter	166.5 mm
Mount Hole	137.4 mm
Mount Depth	80.3 mm
Weight	770 gram

CROSSOVER, SINGLE AMP OR BI AMP

- 3000 Hz, 12 dB Linkwitz-Riley
- Polypropylene capacitors and air core inductors
- 7 position tweeter loudness adjustment
- Tweeter overload protection
- Dimensions: 131 x 84 x 38 mm

POINT SOURCE TWEETER

- 25 mm Black Aluminum
- 4 Ohm

